



Symbol MiniScan MS32XX Series

Fixed Mount Scanner



FEATURES

Compact size

Multiple mounting and interface options provide significant flexibility in the design of your kiosk

High speed omni-directional scan pattern

Build your device with the confidence that even novice users can scan items quickly and accurately

Generates four different scan patterns: omni-directional, semi-omni-directional, raster and single line scan patterns

Enables you to select the best scan pattern for your application

Rugged, durable housing with exit window, integrated beeper, LEDs, decoder and a variety of interfaces including RS-232, USB and Synapse

Gives you plug-and-play installation to reduce your development time and speed your time to market

Plug-and-play module for fast, easy self-scanning integration

The Symbol MS32XX is a member of the MiniScan family of fixed mount scanners specifically designed for kiosks as well as other standalone and OEM applications. The Symbol MS32XX high performance scan module delivers speedy plug-and-play installation in your OEM device — even if you don't have the in-house technical resources for scanner integration. The omni-directional scan pattern minimizes the need for precise positioning of 1D symbols and helps you create intuitive self-scanning applications.

In industries like retail and hospitality, the Symbol MS32XX makes it easier for you to enrich your high-traffic kiosks with customer-centric, self-scanning applications.

How to create the ideal self-scanning applications faster

All of the robust features in the Symbol MS32XX are easy to program and configure, enabling you to cut your development time and bring your product to market faster. With a rugged durable housing, exit window, integrated beeper and interface options, the Symbol MS32XX enables your

project teams to quickly and confidently integrate high-performance 1D and 2D bar code data capture into many self-scanning applications. The Symbol MS32XX delivers a high-speed omni-directional scan pattern that minimizes the need to position 1D bar codes resulting in quick, accurate scanning by any user — novice or expert.

Proven technology to enhance your solutions

With millions of installations worldwide, our OEM devices are proven to deliver high reliability and superior performance, ensuring the accurate and quick capture of data and images in your mission-critical applications and devices. In addition, an easy-to-integrate design and expert assistance from our world-class OEM support team enable you to bring your systems to market quickly and cost effectively. And since even the most intelligent products require a maintenance plan and a support strategy, we offer superior services to help you maximize uptime and maintain peak performance.

For more information about the Symbol MS32XX, access our global contact directory at www.symbol.com/contact or visit us on the web at www.symbol.com/ms32xx

SPECIFICATION SHEET

SYMBOL MINISCAN MS32XX SERIES
Fixed Mount Scanner

Sealed to IP54 standards; protects against water and dust

Ensures reliable
performance in rough
conditions

Reads 1D and 2D symbols including PDF417, MicroPDF, Reduced Space Symbology®

Versatile bar code data
capture in any environment

Retrocollective optical system provides high ambient light immunity

Bright scan pattern ensures
visibility and ease of use,
improving productivity at
the point of activity

Easy-to-program simple serial interface (SSI)

Provides quick and
easy interface (SSI)
communication with
advanced features and
functionality between
scanner and host

Applications

Department and convenience stores; supermarkets; warehouse clubs

Kiosks; gift registry; listening stations; loyalty/incentive programs; customer service
and price verification

Airports and hospitality

ATMs and self check-in/check-out

Symbol MS32XX Specification Highlights

Physical Characteristics

Dimensions (maximum): 1.98" H x 2.41" W x 3.60" L

Weight: 4.97 oz /140.89 gm

Performance Characteristics

Light Source: Visible laser diode 650 nm

Scan Rate: 640 scans/sec (nominal)

Scan Angle:
Horizontal: Cyclone 34°; Raster 34°
Vertical: Cyclone 34°; Raster 12.5°

Scan Patterns: Linear, smart raster and omni-directional

Minimum Print Contrast: 35% absolute dark/light reflectance differential (PDF)
35% absolute dark/light reflectance differential (1D)

Symbologies: PDF417, MicroPDF, UPC/EAN, Code 39, I 2 of 5,
Code 128, Codabar, MSI Plessey, RSS and
Composite Codes

Programmable Parameters: Laser On Time, Aim Duration, Power Mode, Trigger
Mode, Bidirectional Redundancy, Symbology types/
lengths, Data formatting, Serial Parameters, Beeper
Tone, Scan Angle, Pattern Controls

Interfaces: MS3204: RS232
MS3207: TTL RS232, USB, Synapse

User Environment

Ambient Light: Artificial: 450 ft. candles (4,844 LUX)
Sunlight: 8000 ft. candles (86,112 LUX) with
correct enclosure

Operating Temperature: -22° to 122° F /-30° to 50° C

Storage Temperature: -40° to 158° F /-40° to 70° C

Environmental Sealing: IP54

Humidity: 5% to 95% noncondensing

Power: MS3204:
Input Voltage: 5.0 VDC $\pm$ 10%
Input Current: 250 mA typical
Standby Current: 25 +/- 5mA
MS3207:
Input Voltage: $\pm$ 5.0 VDC $\pm$ 10%
Input Current: 250 mA typical
Standby Current: 45 +/- 5mA

Drop Specification: Unit functions normally after multiple 30 in./76 cm
drops to concrete

Regulatory


Laser Classification: CDRH Class II, IEC Class 2

Electrical Safety: Certified to UL1950, CA C22-2 NO950 ENG60950/IEC950


EMI/RFI: FCC Part 15 Class B, ICES-003 Class B European
Union EMC Directive, Australian SMA

Environmental: ROHS-compliant

Symbol MS32XX 1D Decode Zone



Symbol MS32XX 2D Decode Zone



MOTOROLA

motorola.com

Part number SS-MS32XX. Printed in USA 07/07. MOTOROLA and the Stylized M Logo and SYMBOL and the SYMBOL Logo are registered in the US Patent & Trademark Office. All other product or service names are the property of their respective owners. ©2007 Motorola, Inc. All rights reserved. For system, product or services availability and specific information within your country, please contact your local Motorola office or Business Partner. Specifications are subject to change without notice.